

DC 4710 NL

SIZE: 4.69 in. sq. x 1.0 in.
119mm sq. x 25.4mm

AIRFLOW: 50-90 CFM

PRESSURE: .06-18 in. of water
1.52-4.57mm of water



ENGINEERING DATA

Weight	7.7 oz. (220g)
Noise	25-39 dBA
Impeller	UL94V-O Reinforced Plastic
Venturi	UL94V-O Reinforced Plastic
Bearings	Sealed Ball Bearings
Lead Wire	AWG 24, Red/Black UL1007 CSA TR-64
Temperature Range (Operating)	-10°C to +60°C
Insulation Resistance	10 Megohms minimum @500 VDC
Dielectric Strength	700 VAC for 3 secs. or 500 VAC for 1 min.
Insulation	Class A
Safety	Electronic Locked Rotor Protection Polarity Protection Auto Restart

SPECIFICATIONS

MODEL NUMBER	VOLTS	VOLTAGE RANGE	WATTS	mAMPS	SPEED	NOISE dBA	PRESSURE	CFM	
4710 NL 04W	B10	12	6-13.8	1.44	120	1400	25	.06	50
	B20	12	6-13.8	1.80	150	1600	29	.08	60
	B30	12	6-13.8	2.88	240	1900	34	.11	70
	B40	12	6-13.8	4.08	340	2150	36	.14	80
	B50	12	6-13.8	6.84	570	2400	39	.18	90
4710 NL 05W	B10	24	10-27.6	1.44	60	1400	25	.06	50
	B20	24	10-27.6	2.16	90	1600	29	.08	60
	B30	24	10-27.6	2.88	120	1900	34	.11	70
	B40	24	10-27.6	4.08	170	2150	36	.14	80
	B50	24	10-27.6	5.76	240	2400	39	.18	90